

#### Standard Features:

- **FD 676** - Tractor feed, slitters and base
- **FD 680** - FD 676 with an imprinter

#### Options:

- Center slit, static eliminator
- Cylinders for 2-up printing
- Tri-color ink roll, vertical folder
- Power drop stacker, cover lock
- Merger for 2-up forms
- Photo-cell counter (6-digit)
- On/off key switch, crash imprinting
- Last form shut-off switch

**PAPER WEIGHT:** Up to 140 lb. card stock,  
up to 8 parts



Three levels of performance are available to process continuous form documents. The Low Volume Series processes at speeds of 0 to 200 feet per minute. The Medium Volume Series processes at speeds of 15 to 350 feet per minute and is capable of handling up to 17" long forms. The High Volume Series operates at speeds up to 500 feet per minute. All three Series offer a wide array of options to meet individual customer needs. The Low and Medium Volume Series can be used up to five hours per day / five days a week. The High Volume Series is capable of continuous operation seven days a week.

Distributed by **LASER-FORMS.COM**  
100 Main St Ste 222, Dover NH 03820  
www.laser-forms.com info@laser-forms.com

**1-800-777-7359**

<b>SPECIFICATIONS</b>	Speed:	Variable, 30 - 500 feet/minute
	Form Size:	2 3/4" - 19 1/4" (slitting) width 2 3/4" - 17" (non-slitting) width 2 3/4" - 17" length
	Power:	115 Volts AC 50/60 Hz.
	Weight:	FD 676 & FD 680 - 428 lbs.
	Dimensions:	58"L x 41"W x 56"H (w/ base)
	Certifications:	UL

## MEDIUM VOLUME SERIES

### Standard Features:

- **FD 566** - Tractor feed, slitters, base
- **FD 666** - Tractor feed, slitters, base (17" max. form length)
- **FD 668** - FD 666 with an imprinter

### Options:

- Imprinter, center slitter
- Dust cover, tri-color ink roller
- Cylinder for 2-up printing
- Extra wide margin trimmers
- Photo cell counter (6-digit)
- Last form shut-off switch (666 & 668)
- Imprint modules, power drop stacker
- Merger for 2-up forms

**PAPER WEIGHT:** 100 lb. total, up to 4 parts  
(none exceeding 60 lb. tag stock)

## LOW VOLUME SERIES

### Standard Features:

- **FD 544** - Variable speed, friction feed
- **FD 546** - Variable speed, friction feed, slitters
- **FD 548** - FD 546 with base
- **FD 550** - Tractor feed, slitters and base
- **FD 552** - FD 550 with imprinter

### Options:

- Center slitter, static eliminator
- Cylinders for 2-up printing
- Tri-color ink roll, vertical folder
- Power drop stacker, cover lock
- Merger for 2-up forms, dust cover
- Photo-cell counter (6-digit)

**PAPER WEIGHT:** 100 lb. total, up to 4 parts  
(none exceeding 60 lb. tag stock)


**MODEL FD 566**



**Medium Volume Series**

<b>SPECIFICATIONS</b>	Speed: Variable, 15 - 350 feet/minute
	Form size: 2 3/8" - 16" width 2 3/4" - 12" length - Up to 17" (666 & 668)
	Power: 115 Volts AC 50/60 Hz
	Weight: 193 lbs. (566) - 352 lbs. (666 & 668)
	Dimensions: 58"L x 41"W x 56"H (w/base)
	Certifications: UL

**MODEL FD 550**



**Low Volume Series**

<b>SPECIFICATIONS</b>	Speed: Variable, 0 - 200 feet/minute
	Form size: 2 3/8" - 16" width 2 3/4" - 12" length
	Power: 115 Volts AC 50/60 Hz
	Weight: FD 544 -105 lbs. Base - 88 lbs.
	Dimensions: 59" L X 32"W X 56.5"H (w/base)
	Certifications: UL